

CLASSIC 500 TRIBUTE BLACK

TECHNICAL SPECIFICATIONS



THE LAST OF THE
500



ENGINE

Type	Single cylinder, 4 stroke, spark ignition, air-cooled, fuel injection
Displacement	499cc
Bore x stroke	84mm x 90mm
Compression ratio	8.5 ± 0.3 : 1
Maximum power	20.3 kW at 5250rpm
Maximum torque	41.3 Nm @ 4000 rpm
Ignition system	Digital electronic ignition
Clutch	Wet, multi-plate
Gearbox	5 speed constant mesh
Lubrication	Wet sump
Engine oil	15 W 50 API, SL grade & above, JASO MA 2
Fuel supply	Electronic fuel injection
Air cleaner	Paper element
Engine start	Electric/kick

CHASSIS & SUSPENSION

Type	Single downtube, using engine as stressed member
Front suspension	Telescopic, 35 mm forks, 130 mm travel
Rear suspension	Twin gas charged shock absorbers with 5-step adjustable preload, 80 mm travel

DIMENSIONS

Wheelbase	1360 mm
Ground clearance	140 mm
Length	2140 mm
Width	800 mm (without mirrors)
Height	1080 mm (without mirrors)
Kerb weight	195 kg (with 90% fuel & oil)
Fuel capacity	13.5 ± 0.5 litres

BRAKES & TYRES

Tyres front	90/90-19 M/C 52V
Tyres rear	110/80V 18 M/C 58V
Brakes front	280 mm disc, 2-piston caliper
Brakes rear	240 mm disc, single piston caliper
ABS	Dual channel

ELECTRICALS

Electrical system	12 volt - DC
Battery	12 volt, 12 Ah
Head lamp	12V, 60 W / 55 W, HALOGEN
Tail lamp	12V, P21/5W
Turn signal lamp	12V, 10W X 4nos

COLOURS



Tribute black

