MANA

ROYAL ENFIELD

HIMALAYAN

ALL ROADS. NO ROADS.

WHAT'S NEW?

1- BLACK RALLY DUAL SEAT

2- BLACK RALLY HANDGUARDS

3- RALLY MUDGUARD

4- MANA BLACK LIVERY

5- WIRE-SPOKED TUBELESS WHEELS

ENGINE

Type	Liquid cooled, Single cylinder, DOHC, 4 Valves
Bore x Stroke (in mm)	84 mm x 81.5 mm
Displacement	451.65cc
Compression Ratio	11.5:1
Maximum Power	29.44 kW @ 8000 rpm
Maximum Torque	40 nm @ 5500 rpm
Idle RPM	1300
Starting system	Electric start
Lubrication	Semi-dry sump
Engine Oil Grade	10W40 API SN, JASO MA2, Semi Synthetic
Clutch	Wet multiplate, Slip & assist
Gearbox	6 speed
Fuel injection	Electronic Fuel Injection, 42 mm Throttle body, Ride by Wire System

CHASSIS & SUSPENSION

Type	Steel, Twin spar tubular frame
Front suspension	Upside Down Fork, 43 mm
Front Wheel Travel	200 mm
Rear suspension	Linkage type mono-shock
Rear Wheel Travel	200 mm

DIMENSIONS

Wheelbase	1510 mm
Ground Clearance	230 mm
Length	2285 mm
Width	900 mm
Height	1316 mm
Seat Height	860 mm
Dry Weight	181 kg
Kerb Weight (90% Fuel + Oil)	195 Kg
Payload with Standard Equipment	199 Kg
Fuel Capacity	17.0 Litres

BRAKES & TYRES

Tyres Front	90/90-21"
Tyres Rear	140/80 R 17"
Brakes Front	Hydraulic Disc Brake, 320 mm Ventilated Disc, Double piston caliper
Brakes Rear	Hydraulic Disc Brake 270 mm Ventilated Disc, Single piston caliper
ABS	Dual Channel ABS, Switchable

ELECTRICALS

Electrical System	12V
Battery	12 V, 8 Ah
Headlamp	LED Headlamp
Tail Lamp Turn Signal Lamp	Integrated turn & Tail Lamp, All LED
Other Equipment	Ride modes, USB type C charging point
Cluster	4 inch round TFT display with phone connectivity, Full Map Navigation (powered by Google Maps), Media controls
Fuel consumption	3.43l/100 km
Co2	82.82 g/km
Pass by noise (drive by)	77 dB(A)
Stationary noise	90.0 dB(A) @ 4000 rpm

Standard fitment includes: Black Rally Handguards, Black Rally Seat, Rally Mudguard, Wire-spoked Tubeless Wheels

ROYAL ENFIELD

HIMALAYAN

ALL ROADS. NO ROADS.